
















60.4"×47"	DPN (LD-2)		32(113)~37(131)	91(201)~98(216)	
	DC		L 119(47) 110(43)	767 LD	1224(2700)
		L' 156(62) 148(58)			
			W 153(60) 140(55)	777 LD	1224(2700)
			H 163(64) 143(56)		
			—		
60.4"×96"	DQF (LD-8)		7.1(251)	140(309)	
	IC DC		L 244(96) 234(92)	767 LD	2449(5400)
		L' 318(125) 313(123)			
			W 153(60) 140(55)		
			H 163(64) 154(61)		
			6A		
60.4"×61.5"	AKE AVE (LD-3)		3.9(138)~4.4(155)	85(187)~158(348)	
	IC	GARMENT TYPE AVAILABLE	L 157(62) 147(58)	7 LD	1587(3500)
			L' 201(79) 191(75)	767 LD	1587(3500)
			W 153(60) 140(55)	777 LD	1587(3500)
			H 163(64) 157(62)	10 LD	1587(3500)
			8		11 LD 1587(3500)
			—		
60.4"×61.5"	DKN DVN (LD-3)		3.9(138)~4.1(145)	102(226)~138(304)	
	DC	GARMENT TYPE AVAILABLE	L 157(62) 150(59)	7F LD	1587(3500)
			L' 201(79) 191(75)	7LR LD	1496(3300)
			W 153(60) 140(55)	7SR LD	1451(3200)
			H 163(64) 142(56)	767 LD	1587(3500)
			—		777 LD 1587(3500)
			—		10 LD 1587(3500)
			—		11 LD 1587(3500)
			—		
60.4"×125"	DLF (LD-6)		8.9(314)	164(362)~191(421)	
	IC DC	DOOR TYPE : CANVAS or SOLID	L 318(125) 305(120)	7F LD	3175(7000)
			L' 406(160) 398(157)	7LR LD	2993(6600)
			W 153(60) 140(55)	7SR LD	2903(6400)
			H 163(64) 155(61)	777 LD	3175(7000)
			—		10 LD 3175(7000)
			—		11 LD 3175(7000)
			6		

60.4"×61.5"	MVN (LD-3)		3.7(131)		See DKN/DYN (1)Thermal Insulated 保冷 (2)No Temp Control 温度管理不可 (3)Coolant:COOLAIR/DRYICE 冷風ユニット使用				
			L	157(62)		131(52)			
			L'	200(79)		178(70)			
			W	153(60)		130(51)			
			H		161(63)	131(52)			
	DC		320(705)						
60.4"×61.5"	MKN (LD-3)		3.8(134)		See DKN/DYN (1)Thermal Insulated by Polystyrene panel at the inside surface 簡易保冷 (2)No Temp Control 温度管理不可				
			L	157(62)		137(54)			
			L'	201(79)		191(75)			
			W	153(60)		143(56)			
			H	163(64)		147(58)			
	DC		145(320)~154(339)						
60.4"×61.5"	RKN (LD-3)		3.0(106)		See AKE/AVE (1)Refrigerated (保冷) (2)InsideTemp:-5°C~10°C (23°F~50°F) (3)Eff Temp:24HRS (4)Coolant:DRY ICE 35k/77L				
			L	157(62)		125(49)			
			L'	201(79)		180(71)			
			W	153(60)		125(49)			
			H	163(64)		133(52)			
				IC			269(593)~274(604)		
60.4"×96"	MQP (LD-4)		4.9(173)		767 LD 2449 (5400) (1)Thermal Insulated by Polystyrene panel at the inside surface 簡易保冷 (2)No Temp Control 温度管理不可				
			L	244(96)		233(92)			
			W	153(60)		140(55)			
			H	163(64)		147(58)			
				DC			200(440)		
88"×125"	MAP (LD-7)		7.5(245)~8.1(286)		See UAP (1)Refrigerated (保冷) (2)InsideTemp:-5°C~10°C (23°F~50°F) (3)Eff Temp:24HR S (4)Coolant:DRY ICE 35k/77L (5)No Dry Ice Gas Inside				
			L	318(125)		294(116)			
			W	224(88)		196(77)			
			H	163(64)		139(55)			
				IC			580(1279)~720(1587)		

88" X 125"	PAG P1P P1G		—		108(238)~134(295)		
			L	318(125)	295(116)	*7F MD	6804(15000)
IC	DC		W	224(88)	201(79)	**7 LD	4626(10200)
			H	*244(96) **163(64)		**767L LD	5102(11250)
					**777 LD	5551(12240)	
					**10 LD	4670(10296)	
			*2A **5		**11 LD	6033(13300)	
88" X 125"	XAU		—		176(388)		
			L	318(125)	288(113)	*7F LD	4626(10200)
			L'	*457(180) **391(154)		*7LR LD	3753(8275)
			W	224(88)	194(76)	*7SR LD	3615(7970)
			H	163(64)		**777 LD	4626(10200)
						**10 LD	4626(10200)
IC					**11 LD	4626(10200)	
96" X 125"	PMC PQP P6P		—		132(291)~140(309)		
			L	318(125)	295(116)	*7F MD SIDE DOOR	6804(15000)
			W	244(96)	220(87)	**7F MD	6804(15000)
			H	*300(118) **244(96) ***163(64)		***7 LD	5035(11100)
						***767 LD	5102(11250)
						***777 LD	6055(13350)
IC	DC		*2H **2 *** —		***11 LD	5148(11350)	
96" X 196"(16FT)	PZA	 DOUBLE DECK CAR TRANSPORTER AVAILABLE	—		352(776)		
			L	498(196)	484(191)	7F MD	
			W	244(96)	230(91)	NORMAL USE	11340 (25000)
			H	244(96)			CAR TRANSPORT
						13L/R OR 14L/R	7403 (16320)
			IC				
96" X 238.5"(20FT)	PGA P7E PGE (M-2)		—		530(1168)~734(1618)		
			L	606(239)	592(233)	7F MD	11340 (25000)
			W	244(96)	230(91)		
			H	244(96)			
			IC			1	